

Philips  
Stereo Y cable

1,5 m

3.5 mm(M) - 2 RCA(M)

SWA7527W



## Ensure a reliable connection

with this stereo "Y" cable

Depend on this cable to provide you with a reliable audio connection between components.

### Enjoy good audio quality

- High purity copper conductor for reliable signal transfer
- Signal degradation is minimized with gold plated connectors

### Easy installation

- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use

### Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

### Protects against signal loss

- Bare copper shielding

# PHILIPS

sense and simplicity

Stereo Y cable  
1,5 m 3.5 mm(M) - 2 RCA(M)

## Specifications

### Inner Carton

- Gross weight: 0.400 kg
- Inner carton (L x W x H): 24.4 x 15.5 x 10.2 cm
- Nett weight: 0.320 kg
- Tare weight: 0.080 kg
- EAN: 87 12581 41873 1
- Number of consumer packagings: 4

### Outer Carton

- Gross weight: 2.400 kg
- Outer carton (L x W x H): 34.0 x 26.4 x 34.0 cm
- Nett weight: 1.920 kg
- Tare weight: 0.480 kg

- EAN: 87 12581 41874 8
- Number of consumer packagings: 24

### Packaging dimensions

- Packaging dimensions (W x H x D):  
9.4 x 23.6 x 3.8 cm
- Gross weight: 0.100 kg
- Nett weight: 0.080 kg
- Tare weight: 0.020 kg
- EAN: 87 12581 41866 3
- Number of products included: 1
- Packaging type: Blister

SWA7527W/I0

## Product highlights

### Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

### Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

### Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

### Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

### Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

### Gold plated connectors

High quality connectors which minimize signal loss.

### Bare copper shielding

Bare copper shielding protects against signal loss.

### High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.



Issue date 2008-11-09

Version: 2.0.6

12 NC: 8670 000 39465  
EAN: 87 12581 41866 3

© 2008 Koninklijke Philips Electronics N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips  
Electronics N.V. or their respective owners.

[www.philips.com](http://www.philips.com)